

United States Patent 1191

Horsch

[56]

[11] Patent Number: (45) Date of Patent:

5.865,700 Feb. 2, 1999

[54] HYDRO-MECHANICAL TRANSMISSION

[75] Inventor: Joachim Horsch, Lombard, Ill.

[73] Assignee: Case Corporation, Racine, Wis.

[21] Appl. No.: 847,195

[22] Filed: May 1, 1997

[51] Int. Cl.⁶

..... 475/72, 76, 78, [58] Field of Search

475/80, 81, 82; 180/243, 307, 53.1; 56/12.8, 10.1, 11.1, 10.8

..... F16H 47/04

References Cited

U.S. PATENT DOCUMENTS

3,396,607	8/1968	Ross .
3,714,846	2/1973	Louis et al 475/82 >
3,744,344	7/1973	Oisen et al 475/82 >
3,796,111	3/1974	Schauer 475/82 2
3,903,756	9/1975	Hamma 475/82 ≯
4,019,404	4/1977	Schauer 475/82
4,138,907	2/1979	Melles 475/72 >
4,259,881	4/1981	Meyerle 475/72
4,348,855	9/1982	De Pauw et al 56/10.2 >
4,471,668	9/1984	Elsner 475/7:
4,487,002	12/1984	Kruse et al 56/10.2
4,694,648	9/1987	Beck, Jr
4,913,004	4/1990	Panoushek et al

5,024,278 5,494,142 6/1991 Shuknecht 56/12.8 X 2/1996 Kale . 5.505.267 4/1996 Orbach et al. . 5,549,185 8/1996 Kale .

FOREIGN PATENT DOCUMENTS

0 444 472 A2 2/1991 European Pat. Off. . 4311 084 C1 4/1993 Germany .

Primary Examiner-Khol Q. Ta

Attorney, Agent, or Firm-Foley & Lardner ABSTRACT

A hydro-mechanical transmission for an agricultural work vehicle is provided including a motor, a clutch and a differential assembly. The clutch which is rotatably supported by a housing includes first and second input shafts and a first output shaft. The first output shaft is configured to selectively couple to the first and second input shafts. The motor is coupled to the second input shaft, and the differential assembly which is rotatably supported by the housing is coupled to the first output shaft. The differential assembly includes a third input shaft coupled to the first output shaft, and a fourth input shaft coupled to the motor, and a second output shaft. The speed of the second output shaft is a combination of the speeds of the third and fourth input chafte

28 Claims, 3 Drawing Sheets

